



# UNITEDSEATS

your global seat supplier

## SAFETY BELTS



For more information about UnitedSeats  
visit **[www.unitedseats.com](http://www.unitedseats.com)**  
or e-mail us at [info@unitedseats.com](mailto:info@unitedseats.com)



## ON.151250

Static 2-point seat belt adjustable

Belt length: 120 cm

Flex buckle 28 cm

Belt colour: black

With fitting kit



## ON.150754

Automatic 2-point seat belt ALR

Belt length: 120 cm

Buckle 15 cm

Belt colour: black

With fitting kit



## ON.150810

Automatic 2-point seat belt ALR

Belt length: 120 cm

Buckle 12 cm

Belt colour: black

With fitting kit



## ON.150763

Automatic 2-point seat belt ALR

Belt length: 120 cm

Flex buckle 24 cm

Belt colour: black



## ON.151100

Automatic 2-point seat belt ALR

Belt length: 120 cm

Flex buckle 22 cm

Belt colour: black

With fitting kit





## ON.150756

Automatic 2-point seat belt ALR

Belt length: 120 cm

Buckle 15 cm

Belt colour: orange

With fitting kit



## ON.151000

Automatic 2-point seat belt ALR

Belt length: 120 cm

Buckle 15 cm + Switch NO/NC

Belt colour: black

With fitting kit



## ON.150756 S

Automatic 2-point seat belt ALR

Belt length: 120 cm

Buckle 15 cm + switch NO/NC

Belt colour: orange

With fitting kit



## ON.150757 S

Automatic 2-point seat belt ALR

Belt length: 120 cm

Buckle 15 cm + switch NO/NC

Belt colour: yellow

With fitting kit



## ON.150775

Automatic 2-point seat belt ALR

Belt length: 120 cm

Buckle 15 cm + switch NO/NC

Belt colour: red

With fitting kit





## ON.150900

Automatic 2-point seat belt ELR

Duo sensitive

Belt length: 220 cm

Flex buckle 27 cm

Belt colour: black

With fitting kit



## ON.151003

Automatic Securon 2-point seat belt ELR

Duo sensitive

Belt length: 110 cm

Flex buckle 25 cm + switch NO/NC

Belt colour: black

With fitting kit



## ON.151005

Automatic Securon 2-point seat belt ALR

Belt length: 110 cm

Fixed buckle 15 cm + switch NO/NC

Belt colour: black

With fitting kit



## ON.151006

Automatic Securon 2-point seat belt ALR

Belt length: 110 cm

Fixed buckle 15 cm + switch NO/NC

Belt colour: orange

With fitting kit



## ON.150745

Double seat belt set ALR

Belt length: 120 cm (x2)

Belt colour: black





## ON.151102

Static 3-point seat belt adjustable

Belt length: 230 cm

Flex buckle 30 cm

Belt colour: black

With fitting kit



## ON.151103

Automatic 3-point seat belt ELR

Belt length: 270 cm

Flex buckle 22 cm

Belt colour: black

With fitting kit



## ON.151106

Automatic 3-point C1 seat belt ELR

Belt length: 270 cm

Flex buckle 30 cm

Belt colour: black

With fitting kit



## ON.151107

Automatic 3-point seat belt ELR

Belt length: 360 cm

Fixed buckle 15 cm

Belt colour: orange

With fitting kit



## ON.151108

Automatic 3-point seat belt ELR

Belt length: 350 cm

Flex buckle 30 cm

Belt colour: yellow

With fitting kit





## ON.151109

Automatic 3-point seat belt ELR

Belt length: 310 cm

Flex buckle 30 cm

Belt colour: black

With fitting kit



## ON.150855

Static 4-point seat belt

Adjustable in length

No FIA approval

Belt colour: red



## ON.151368

Seat belt lock

Flex buckle 30 cm



## ON.151365

Seat belt lock

Flex buckle 25 cm



## ON.151367

Seat belt lock

Flex buckle 22 cm





## **ON.151360**

Seat belt lock

Buckle 15 cm



## **ON.151351**

Seat belt lock

Buckle 12 cm



## **ON.151415**

Seat belt lock

Buckle 15 cm + NO/NC switch



## **ON.151420**

Seat belt lock extension

Length: 48 cm

Belt colour: black







# UNITEDSEATS

## your global seat supplier

### Product information

Our products are manufactured, tested and approved to European /National Standards as and when required, i.e. ECE R16, SAE J386 & ISO 6683. Identification of the relevant standard is carried on the product.


- ECE Regulation 16:** Restraint for cars, coaches etc. for UK and European road use
- SAE J386:** Pelvic Restraint Systems for off road work Machines
- ISO 6683:** Seat Belts & Seat Belt Anchorages (earth moving machinery)

### Explanation of seat belts variants

**ALR** = Automatic Locking Retractor

**ELR** = Emergency Locking Retractor (Duo Sensitive)

**Approval (E & e)** E = ECE R16 e = EEC Directive 77/541



**ECE** = Economic Commission for Europe

**EEC** = European Economic Community

**ISO** = International Organisation for Standardisation

**A** = 3 or 4 point mounting Lap and Diagonal Belt

**B** = 2 point mounting Lap Belt

**r** = Safety belt with retractor

**3** = Automatic locking retractor

**4** = Emergency locking retractor

**m** = Multiple sensitivity

### CE Marking

Seat Belts are independently tested and certified to European Directive 77/541 and/or Regulation 16 - they should not be CE marked. The latter can be confirmed by any Notified Body, i.e. B.S.I., C.S.I. etc.

CE marking is in many cases a subjective analysis with limited or no testing and no guaranteed base line performance.

### Seat belts save lives - If they are in good condition!

In an accident a seat belt becomes a life saver. But wear & tear and abuse all cause the seat belt to deteriorate. Holes, cuts, fraying or fluffing weaken the belt, can obstruct its operation, and/or cause slackness. Loads in an accident can reduce the effectiveness of the belt. In a severe impact the seat belt loading is approximately equal to the weight of a three tonne elephant! After an accident, in all cases, the complete seat belt should be replaced.

### Safety instructions

- These instructions should be passed to the owner/driver.
- The belt is designed for use by one person and must not be put around a child seated on a persons lap.
- It is important to wear the belt on each journey.
- The belt is suitable for restraining most child seats and boosters.
- It is not intended for children under 6 years of age unless used with other approved restraints.
- The belt should at all times be adjusted and used in accordance with the instructions. No excessive slackness should be present.
- Once installed the diagonal should pass across the centre of the shoulder and the buckle should lie just on or below the hip.
- Avoid twisting the webbing during use. Webbing must not be allowed to chafe, i.e. against sharp edges.
- Do not make alterations or additions to the belt. If in doubt, consult the manufacturer.
- Belts that have been cut, frayed, damaged or stressed through impact should be replaced. After impact, the car anchorage points should also be checked.
- To clean use warm soapy water only. Do not use chemical cleaners, bleach or dye. Contamination with petrol, grease and acid will be detrimental.
- Periodic inspection of the installation will ensure reliable service of the seat belt.

## UNITEDSEATS

Schrijnwerkersstraat 10

3334 KH Zwijndrecht

The Netherlands

T: +31 (0)88 - 0158 700

E: [info@unitedseats.com](mailto:info@unitedseats.com)

I: [www.unitedseats.com](http://www.unitedseats.com)

We unite  
your seat